



## achesiv

floor eav

## Floorwise supply the flooring professional with a quality and versatile range of adhesives & levelling compounds which won't let you down on the job!

The perfect floor needs a perfect base and our range of products cover every need in order to achieve this! Then what you must have is an adhesive that holds fast and lasts the course. Floorwise won't let you

down, and absolutely **won't come unstuck** when it comes to product quality, availability or supply!





pages **3-4 levelling & smoothing** compounds

page 5 levelling & smoothing compound suitability chart

pages **6-7 flooring** adhesives

pages 8-9 cartridge adhesives & sealants

pages 10-11 spray adhesives

page 12-13 canister spray adhesives page 14 adhesive suitability chart

page **15 floorwise distribution** network

wiseup to floorwise quality&value guaranteed

### levelling & smoothing compounds

F5GOLD Pro-Screed Gold 2 Part rapid setting latex polymer levelling & smoothing compound
F5GOLDLL Pro Screed Latex Liquid

A versatile 2 part latex polymer levelling and smoothing compound with excellent flow and adhesion properties. The unique formulation qualities allow the compound to be installed without the need to prime on most sub floors. The ultra fast setting compound can be walked on after as little as 90 minutes and floorcoverings can be installed after just 4 hours. It can applied from depths of 2mm to 12mm in one application and up to 30mm with aggregate. It is moisture tolerant and can be laid under and over DPM's and can be applied over most underfloor heating systems.

Rapid Setting
 Walk on after 90 minutes
 Install floorcoverings after 4 hours

- Excellent flow and application properties
- Suitable for use over old adhesive residues
- Moisture tolerant can be used below and over DPM's
- No priming necessary on most subfloors
- Perfect for timber substrates
- Suitable for use with Underfloor heating systems
- Low odour
- Protein, ammonia & casein free

Pro-screed Gold Control Service Control Contro

Walk on time: **90 minutes** 

Working time: Approximately 20 minutes

Apply Floorcovering: **Typically 4 hours** (3 hours for ceramic tiles)

Compressive Strength: C16 after 28 days

Application Thickness: Featheredge to 10mm unfilled

From 10mm to 30mm filled

(3mm granite chippings)

Coverage: 5-6m<sup>2</sup> @ 3mm per 20kg bag

+ 5L liquid



**5**L





### levelling & smoothing compounds

### F5FEA Pro Screed Feather Edge ultra fine, rapid setting levelling & patch repair compound

An ultra-fine rapid setting, fast drying, high polymer leveling and patch repair compound. The unique formulation truly delivers a feather edge from 0-3mm, perfect for feathering and patching depressions, trowel marks, ridges, gouges and joints in subfloors, as well as smoothing over screw heads and joints between sheets of plywood. With outstanding adhesion properties the compound can be used without a primer and can be applied over most underfloor heating systems.

- Rapid drying
- Install floorcoverings after 15 minutes
- Excellent adhesion properties
- Perfect for timber substrates
- No priming necessary
- Suitable for use with underfloor heating systems
- Protein free

Walk on time: 15 minutes

Working Time: Approximately 10-15 minutes

Apply Floorcovering: After 15 minutes

Application thickness: 0 to 3mm

Coverage: 45m<sup>2</sup> @ 1mm per

10kg bag mixed with 5L water



### levelling & smoothing compound suitability guide

	F5GOLD	F5FEA
Product	IGGED	IJIEA
Size	20Kg & 5L	10Kg
Coverage	5-6m² @ 3mm	45m² @ 1mm
_	per 20kg bag+ 5 L liquid	per 10kg bag+ 5 L water
Working time at 20°C	15-20 minutes	15 minutes
Time to foot traffic at 20°C	90 minutes	15 minutes
Time to lay floorcovering absorbent	4 Hours	4F minutes
non absorbent	4 Hours	15 minutes
Application thickness min (mm) unfilled	2 mm	0mm
max (mm) unfilled	12mm	3mm
max (mm) filled	30mm	N/A
Compressive strength 28 day	C16	C12
Flexural strength 28 day	F7	F5
EN 13813 class / EN 1504-3 class	CT-C16-F7	CT-C12-F5
Application method		
Trowel	<b>✓</b>	V
Pump application		
Aeration roller recommended	V	
Product characteristics		
Rapid setting	✓ Walk on - 90 minutes	✓ Walk on - 15 minutes
	install floorcovering 4 hours	install floorcovering 15 minutes
Excellent flow	<b>∨</b>	
Suitable for use over old adhesive residues	<b>✓</b>	
No priming necessary	<b>✓</b>	V
Suitable for rigid timber substrates	V	V
Suitable for use with underfloor heating	<b>v</b>	V
Suitable for biologically sensitive areas	<b>v</b>	<b>V</b>
Suitable for high temperature areas	<i>V</i>	<b>V</b>
Moisture tolerant – can be used below	<b>V</b>	
and above DPM's	V	
Low odour	<b>✓</b>	<b>V</b>
Protein, ammonia & casein free	V	V
Sub floor suitability		
Concrete, sand/cement screeds and other	<u> </u>	V
solid absorbent surfaces	•	•
Power floated concrete	<b>✓</b>	V
Ceramics, porcelain, terrazzo,		
marble, granolithic and other	<b>✓</b>	<b>✓</b>
non absorbent surfaces		
Anhydrite screeds*	<b>✓</b> *	<b>✓</b> *
Old adhesive residues (moisture tolerant)	<b>✓</b>	
Surface DPM, epoxy &		
polyurethane coatings	•	
Flooring grade plywood	<b>✓</b>	V
Rigid timber floors	<i>V</i>	V
Rigid vinyl tiles	<b>✓</b>	<b>∨</b>
Rigid steel/metal	<b>~</b>	
(non flexing & corrosion free)	•	
Flooring grade asphalt/bitumen	<b>✓</b>	<b>∨</b>
Fibre cement sheet & tile back boards	<i>V</i>	<b>✓</b>
Fibreglass	<b>✓</b> *	

\* when primed

### flooring adhesives

### F555 All-purpose Flooring Adhesive

This all-purpose flooring adhesive is an acrylic based, non-staining adhesive formulated to give excellent initial grab and a high quality, durable bond when dry.

Suitable for permanently bonding carpets & vinyl floorcoverings onto a wide variety of subfloors. It is low in VOC's and the adhesive is suitable for application over most underfloor heating systems.

Coverage: approx. 45-55m<sup>2</sup> per 15kg bucket

- Excellent initial grab
- High performance bond
- Great coverage
- Easy application
- Suitable for use with underfloor heating systems
- Low VOC





### F523 Carpet Tile Tackifier

Carpet Tile Tackifier is a solvent free, non staining, acrylic polymer dispersion adhesive formulated to produce a permanent tacky finish when dry.

Suitable for bonding carpet tiles with PVC, polypropylene and bitumen with fibre backings to a wide variety of subfloors; It is low in VOC's and the adhesive is suitable for application over most underfloor heating systems.

Coverage: approx. 140–160m<sup>2</sup> per 15kg bucket approx. 230–250m<sup>2</sup> per 25kg container

- Easily appliedFast drying
- High permanent tack (pressure sensitive)
- Tiles can be lifted and replaced







### flooring adhesives

### **F542 MS Polymer Wood Flooring Adhesive**

The MS polymer wood flooring adhesive is a high performance, flexible, single component, solvent and water-free adhesive for permanent bonding of all types of wood flooring. Compatible with most underfloor heating systems, the advanced polymer adhesive is both safe and clean to use.

Coverage: approx. 16-24m<sup>2</sup> per 16kg bucket. approx. 10 linear metres of 8mm bead per 600ml sausage.

- Permanent elastic bond
- One component
- Rapid curing
- Excellent initial grab
- High performance bond
- Easy application
- Solvent free
- Low VOC
- Suitable for use with underfloor heating systems



### **F538 Water Resistant Wood Adhesive**

This non-plasticised, cross linking PVA emulsion adhesive is specially formulated for wood bonding in all cases where a fast set, high bond strength and excellent water resistance are required. Suitable for virtually all woods, wood decoratives and high pressure laminates. Conforms to BSEN 204:1991:D3 and BS4071 for creep resistance.

Coverage: approx. 60–80 linear metres of 3mm bead per 500ml bottle

- Fast drying
- High initial grab
- High shear strength
- Great temperature resistance

**500**m





### cartridge adhesives & sealants

### F500 Silicone Joint Sealant

This silicone joint sealant is specially formulated for use in providing a waterproof, hygienic, flexible seal, which is resistant to mildew and mould growth.

Coverage: approx. 11 linear metres of a 6mm bead per cartridge

- Interior and exterior applications
- **High movement accommodation**
- **Excellent adhesion**
- Lasts up to 25 years
- **Contains fungicide**

**310** ml

### F579 Fast Set Floor-Fix PU Adhesive


Is a fast setting polyurethane adhesive for both interior and exterior applications. It has super quick grab and excellent grab bond strength suitable for a wide range of materials and surfaces.

Coverage: approx. 40 linear metres of a 3mm bead per cartridge

- Super quick grab adhesive
- Interior/exterior applications
- Excellent bond strength
- Bonds to most substrates

**310** ml







High initial grab

floorwis

mastic

### F577 Floor Fix Mastic Adhesive

Is a high strength, gap filling cartridge adhesive for bonding a wide variety of materials to most surfaces.

Coverage: approx. 11 linear metres of a 6mm bead per cartridge

- High initial grab
- **Excellent gap filling**
- **Excellent bond strength**
- Bonds to most substrates

**310** ml

E floorwise

Interior/exterior

High ement

Lasts

Excellent

vears

Contains

500

wise







### cartridge adhesives & sealants

### **FLE290 Flexy Fix MS Polymer Adhesive**

An extremely versatile, high performance flexible, rapid curing MS polymer adhesive for bonding a wide variety of materials to most surfaces. Approved for direct stick stair nosings applications and compatible with most underfloor heating systems, this advanced polymer adhesive is easy and clean to apply.

Coverage: approx. 15 linear metres of a 5mm bead per cartridge

- Permanent elastic bond
- Rapid curing
- Excellent initial grab
- High performance bond
- Easy application
- Solvent free
- Low VOC
- Approved for direct stick stair nosing applications
- Suitable for use with underfloor heating systems







### **F580 Contact Adhesive**

A versatile synthetic rubber/resin contact adhesive for bonding a wide variety of floorcoverings, PVC coving and skirtings to a wide variety of floor & wall surfaces.

Coverage: approx. 27.5m<sup>2</sup> on a single non-porous surface per 5 Litre can

- Fast drying
- High initial grab
- High shear strength
- Great temperature resistance



### **F599 Heavy Duty Spray Adhesive**

This market-leading spray adhesive can be used to fix a wide variety of floorcoverings onto most sub floors.

Coverage: approx. 3m<sup>2</sup> per can onto a single non-porous surface

- Higher solids more adhesive per can
- Higher coat weight more adhesive to the surface
- Excellent bond strength
- Super quick drying

\*Not suitable for highly plasticised Vinyls or PVC

**500**ml





### F592 Contact Spray Adhesive

A versatile synthetic rubber/resin contact adhesive for permanently bonding a wide variety of materials to most surfaces. It has high temperature resistance making it suitable for most underfloor heating systems.

Coverage: approx. 3m² per can onto a single non-porous surface

- High adhesive content
- Excellent bond strength
- High temperature resistance (up to 90°C)
- Quick drying
- Easy to use
- CFC free

\*Not suitable for highly plasticised Vinyls or PVC Contact sprayachesive sarpet carpet iles, will floor coverings, les kirlings & much more lich abgregation in the contact and strength with appearure resistance of 1900.

In the contact adhesive sarpet iles, will floor coverings, les kirlings & much more lich appearure resistance of 1900.

In the contact adhesive sarpet iles, will form the contact and the contact a

**500**ml

### spray adhesives



gth

o use

### **F590 Solvent Cleaner**

A powerful solvent based cleaner to quickly remove adhesive, oils, grease and other organic substances. Perfect for cleaning larger canister guns and hoses.

- Powerful action
- Quick and easy to use

**500**ml

### **F595 Vinyl Spray Adhesive**

Is a plasticiser-resistant adhesive for permanently bonding a variety of floorcoverings, including vinyl and PVC to a wide range of subfloors.

Coverage: approx. 3m² per can onto a single non-porous surface

- Plasticiser resistant
- Excellent bond strength
- Easy to use

**500**ml



### F598 Spray Adhesive

A good all round spray adhesive for permanently bonding a wide variety of floorcoverings onto most subfloors.

Coverage: approx. 3m² per can onto a single non-porous surface

- Strong bond
- Quick drying
- Easy to use

\*Not suitable for highly plasticised Vinyls or PVC

**500**ml





### canister spray adhesives



### **F592C Contact Spray Adhesive**

A versatile synthetic rubber/resin contact adhesive for permanently bonding a wide variety of materials to most surfaces. It has high temperature resistance making it suitable for most underfloor heating systems.

Coverage: approx. 100-150m<sup>2</sup> on a single sided application per 19.5L canister, dependent upon the porosity of the subfloor.

- Superfast spray action
- Long open time
- Great grab
- Strong bond strength
- Great temperature resistance



\*Not suitable for highly plasticised Vinyls or PVC

**19.5** 

**19.5** 

### **F593C Super Contact Spray Adhesive**

A versatile synthetic one part rubber/resin contact adhesive for permanently bonding a wide variety of materials to most surfaces. It is formulated with a high adhesive content which improves the initial grab and final bonding strength. With a high temperature resistance it is suitable for most underfloor heating systems.

Coverage: approx. 100-150m<sup>2</sup> on a single sided application per 19.5L canister, dependent upon the porosity of the subfloor.

- High adhesive content
- Superfast spray action
- Long open time
- Excellent grab
- Strong bond strength
- Great temperature resistance

\*Not suitable for highly plasticised Vinyls or PVC



### canister spray adhesives



### F594C Carpet Tile Tackifier Spray Adhesive

This high solids spray adhesive remains permanently tacky when dried, perfect for holding down carpet tiles, underlays and other floorcoverings which may require uplifting at a later date. Suitable to bonding to a wide variety of subfloors.

Coverage: approx. 300-500m<sup>2</sup> on a single sided application per 19.5L canister, dependent upon the weight of application and porosity of the subfloor.

- Superfast spray action
- High adhesive content
- Fast drying

19.5

- Exceptional coverage
- Low odour
- \* Not suitable for PVC backed carpet tiles

### F7252 Standard Gun for spray canisters

Durable and lightweight gun with versatile interchangeable

**9501** spray tip.

### F7254 Hose for spray canisters

Lightweight yet durable nylon core with synthetic rubber coating. Compete with easy fit connectors.





### F7251 Premium Gun for spray canisters

Strong Aluminium Alloy Body with versatile interchangeable **9501** spray tip.



### F7253 Standard Gun & Wand for spray canisters

Durable and lightweight gun with 47cm extension wand, complete with versatile interchangeable **9501** spray tip.



## adhesives suitability chart

Product    Product   Produ						-61			194		7	3				8	
Application method  Towas	Product	F555	F523	F542	F538	F580	F500	F577	F579	FLE290	F595	F598	F599	F592	F592C	F593C	F594C
Application method  Trong		ize: 15kg :overage: 45-55m²	ize: 15kg/25Kg :overage: 140-160m² -15kg 230-250m² -25kg	ize: 16kg/600ml :overage: 140-160m²-16kg 10 LM-600ml 8mm bead	ize: 500ml coverage: 60-80 LM 3mm bead	ize: 5L :overage: 27.5m² (single side)	ize: 310ml coverage: 11 LM (6mm bead)	ize: 310ml coverage: 11 LM (6mm bead)	ize: 310ml coverage: 40 LM (3mm bead)	ize: 290ml coverage: 15 LM (5mm bead)	ize: 500ml coverage: 3m² (single side)	ize: 500ml :overage: 3m² (single side)	ize: 500ml coverage: 3m² (single side)	ize: 500ml :overage: 3m² (single side)	ize: 19.5L :overage: 100-150m² (single side)	ize: 19.5L coverage: 100-150m² (single side)	ize: 19.5L :overage: 300-500m² (single side)
Troop	Application mothed	ωO	ωO	ø0	SO.	ωO	<b>o</b> O	ဖပ	ဖပ	ωO	ဖပ	ωO	<b>o</b> O	ဖပ	w O	ωO	ဖပ
Brach Carridge gran		V	V	~		~											
Carriogn gain			V														
Standarder State Characteristics    Product Characteristics		_		_					~								
Product characteristics	Spray canister							_			~	V	V	V	V	~	V
Subable for underfloor heading	Bottle				V												
Subable for underfloor heading	Product characteristics																
Place   Plac	Suitable for underfloor heating		-	V	V					V		V	V	V			
Long continger   V						V									V	V	V
Fig. Intelligence				-										V	V	V	V
Direct bonding to subfloor	High initial grab	V															
Themoplastic life	Permanently tacky when dry		V														V
Arbyorine	Thermoplastic tiles	V	V	V		V		V	V	V	V		V	V	V	V	V
Seed																	
Epox 8   Apolyurehran (floor finarles)		_			~			-							-		
Non absorbent concrete    V   V   V   V   V   V   V   V   V												_		_			
Terrazzo, mathle, granolithic etc.																	
Absorbert sand/coment, some and concrete visual vis																	
Test	Absorbent sand/cement,																
Felt Latex																	
Latex																	
Novement																	
														_	-	_	
Jute/cotton/hessian																	
Polypropylene Underlay Felt Felt Felt Felt Felt Felt Felt Felt																	
Polypropylene Underlay Felt Felt Felt Febond (PU foam) Rebond (PU foam) Re																	
Felt																	
Rebond (PU foam) A Polyetrylen foam A Polyetrylen foam A Rubber crumb A Rupy C Rupy PVC A Rupy PVC Rupy PVC Rupy Rupy Rupy Rupy Rupy Rupy Rupy Rupy																	
Rubber and Buller and		-										-	-	-	-	-	
Bitumen/felt A PVC Vinyl / PVC Felt Felt PVC S S S S S S S S S S S S S S S S S S S																	<u> </u>
Bitumer/felt  A  Vinyl / PVC  Felt  PVC  PVC   IN I			<b>A</b>									_	-	_			
PVC			<b>A</b>														<b>A</b>
Felt PVC PVC foam Vinyl composite tile PVC coving & skirting Rubber Rubber Rubber Cork Cork Cork Cork Cork Cork Cork Cor	PVC																
PVC oving composite tile PVC coving & skirting Rubber Rubber Linoleum Jute/hessian Polyester Cork Cork Mood/parquet Block Mosaic Laminate Engineered Solid – small strip Solid – large strip Tongue & groove Gripper, profiles & nosings Aluminium Brass PVCU																	
PVC foam Viryl composite tile																	
Rubber Rubber Linoleum  Jute/hessian Polyester Cork Cork Block Block Laminate Laminate Engineered Solid – large strip Tongue & groove Gripper, profiles & nosings Aluminum Brass PYCU	PVC foam																
Rubber Rubber Linoleum  Jule/hessian Polyester Cork Cork Block Mosaic Laminate Engineered Solid – small strip Solid – large strip Tongue & groove Gripper, profiles & nosings Aluminum Brass PYCU														-			
Rubber Linoleum Julte/hessian Polyester Cork Cork Block Mosaic Laminate Engineered Solid – small strip Solid – large strip Torgue & groove Gripper, profiles & nosings Aluminum Brass PVCU																	
Jute/hessian Polyester Cork Cork Wood/parquet Block Mosaic Laminate Engineered Solid – small strip Tongue & groove Gripper, profiles & nosings Aluminum Brass PVCU	Rubber													•			
Polyester Cork Cork Wood/parquet Block Mosaic Laminate Engineered Solid – small strip Solid – large strip Tongue & groove Gripper, profiles & nosings Aluminum Brass PVCU																	
Cork  Wood/parquet Block Mosaic Laminate Engineered Solid – small strip Solid – large strip Tongue & groove Gripper, profiles & nosings Aluminium PYCU																	
Wood/parquet Block Mosaic Laminate Engineered Solid – small strip Tongue & groove Gripper, profiles & nosings Aluminium PYCU	Cork																
Block Mosaic Laminate Engineered Solid – small strip Solid – large strip Torgue & groove Gripper, profiles & nosings Aluminium Brass PVCU												-					
Mosaic  Laminate  Engineered  Solid – small strip  Solid – large strip  Tongue & groove  Gripper, profiles & nosings  Aluminium  PVCU																	
Engineered  Solid – small strip  Tongue & groove  Gripper, profiles & nosings  Aluminium  PYCU	Mosaic																
Solid – small strip Solid – large strip Tongue & groove Gripper, profiles & nosings Aluminium Brass PVCU																	
Solid – large strip Tongue & groove Gripper, profiles & nosings Aluminium PVCU																	
Gripper, profiles & nosings           Aluminium         Image: Control of the contr	Solid – large strip																
Aluminium         Image: Control of the control o																	
Brass PVCU I I I I I I I I I I I I I I I I I I I																	
	Brass																
	PVCU Wood			-					-	-							



# wiseup to floorwise quality&value guaranteed





### 1 Neil Smith Ltd

Glasgow Tel: 0141 552 1141 sales@neilsmithltd.co.uk

### 2 Provincial Floorcoverings Ltd

Belfast Tel: 028 9075 3202 Fax: 028 9075 3901 salesbelfast@pfl.ie

### 3 Floorwise (North East) Ltd

Birtley, County Durham Tel: 0191 410 7070 Fax: 0191 410 6116 sales@floorwisene.co.uk

#### 4 MCA Floorwise Ltd

Morecambe, Lancashire Tel: 01524 33517 Fax: 01524 381852 sales@mcafloorwise.co.uk

#### **5 Birch Distribution**

Hull

Leeds

Tel: 01482 826654 Fax: 01482 878693 d.ostler@birchdistribution.co.uk

#### **6 Birch Distribution**

Tel: 0113 244 4363 Fax: 0113 244 8665

p.zanetti@birchdistribution.co.uk

#### 7 Provincial Floorcoverings Ltd

Dublin 10 Tel: 00353 (0)1 626 3913 Fax: 00353 (0)1 626 3960 salesdublin@pfl.ie

### 8 Provincial Floorcoverings Ltd 16 BL Flooring Supplies Ltd

Tel: 00353 (0)61 227 100 Fax: 00353 (0)61 227 000

sales@pfl.ie

#### 9 Choice Flooring Ltd

Trafford Park, Manchester Tel: 0161 872 8003 choice\_flooring@yahoo.com

#### 10 Cornerstone Flooring

Doncaster Tel: 01302 835117 Fax: 01302 302542 cornerstonefloor@btconnect.com

### 11 Birch Distribution

Sheffield Tel: 0114 243 1230 Fax: 0114 243 5118 n.maude@birchdistribution.co.uk

#### 12 Woodall Brothers Ltd

Shrewsbury, Shropshire Tel: 01743 441584 Fax: 01743 441629 sales@woodallbrothers.co.uk

### 13 Floorwise D & J Ltd

Southam, Warwickshire Tel: 01926 814922 Fax: 01926 817899 sales@fwdj.co.uk

#### 14 Salesmark Ltd

St Neots, Cambridgeshire Tel: 01480 212888 Fax: 01480 218585 sales@salesmark.co.uk

#### 15 BL Flooring Supplies Ltd

Gloucester Tel: 01452 223355 Fax: 01452 371284 info@blflooring.co.uk

Tel: 0117 955 5454 Fax: 0117 955 2626 info@blflooring.co.uk

### 17 Salesmark West Ltd

Amesbury, Wiltshire Tel: 01980 880933 mail@salesmark-west.co.uk

### 18 Acorn Carpet Accessories

Bromley, Kent Tel: 020 8462 0422 Fax: 020 8462 0927

acorncarpetsacc@btconnect.com

### 19 Salesmark

Lancing, West Sussex Tel: 01903 750522 Fax: 01903 851111 sales@salesmark-floorwise.co.uk

### 20 Fitwell Flooring Ltd

Newton Abbot, Devon Tel: 01626 835935 sales@fitwell.co.uk

### 21 Fitwell Flooring Ltd

Redruth, Cornwall Tel: 01209 214344 sales@fitwell.co.uk



Floorwise House, 22 High Street, Kegworth, Derby, DE74 2DA, UK

Tel: +44 (0)1509 673974 Fax: +44 (0)1509 674841



# When it comes to flooring installation, **Floorwise** is the name for **quality** and **value**!

For over 35 years Floorwise has been the number one choice for flooring professionals.

Reliable service, through an exclusive network of distributors, and the consistent quality of our products has earned Floorwise an enviable reputation.


Floorwise strives to deliver excellence in innovation too, with a continuous development program aimed at meeting the evolving needs of both consumers and the fitters alike.

### for **sales** and **enquiries** contact:

## wiseup to floorwise quality&value guaranteed



Floorwise offer a wide range of quality foam, rubber and felt underlays, delivering varying levels of performance & suitable for every type of carpet.



Crafted from premium quality materials, Floorwise Profiles are easy to handle and deliver longer lasting use.



Sourced from the world's best suppliers, the Floorwise Tools collection brings you the very best to make sure your high standards are upheld.



Ensuring a quality installation for each and every carpet, Floorwise Gripper is made to the highest standards.



Floorwise Stair Nosings, PVC Skirting and trims are made to deliver long lasting performance.