

F595 Vinyl Spray Adhesive

Versatile acrylic based plasticiser **resistant** spray **adhesive** for bonding a **wide range** of **floorcoverings**.

- **Plasticiser** resistant
- **Excellent Bond Strength**
- **Easy to Use**
- **Non** Carcinogenic

Description:

F595 is an acrylic based plasticiser resistant spray adhesive for bonding a variety of floorcoverings.

Uses:

F595 Spray Adhesive is suitable for the permanent bonding of vinyl, PVC, carpets, carpet tiles, cork, paper, underlay, felts and much more.

Sub-Floors:

F595 is suitable to bonding to concrete bases, cement screed, smoothing & levelling underlayment, flooring grade chipboard, hardboard, plywood, stone, terrazzo, quarry tiles, ceramic, brickwork and plaster.



Specification:

Directions for Use:

IMPORTANT

Before using F595 Vinyl Spray Adhesive please refer to the safety guide and data sheet available at www.floorwise.co.uk

All phases of the installation should comply with the latest editions of the following standards:

- BS 8102 Code of Practice for the protection of buildings against water from the ground.
- BS 5325 Code of Practice for the installation of textile floorcoverings.
- BS 8203 Code of Practice for the installation of resilient floorcoverings.

Preparation:

Surfaces to be bonded should be clean, dry and dust free.

Shake can well before use.

Application:

Spray an even coat of adhesive onto one surface. Allow adhesive to become touch dry.

Press floorcovering firmly into place, which will bond immediately.

Allow approximately 30 minutes for adhesive to set.

After use invert can and press nozzles to clear adhesive from spray tip.



Cleaning:

Remove any over spray immediately with Floorwise solvent cleaner or minimum of white spirit.

Adhesive Type:	Acrylic
Colour:	Light Beige
Flashpoint:	Highly Flammable
Coverage:	Approximately 3m ² per 500ml can on a single, smooth, non-porous surface
Application Temperature:	+5°C - +30°C
Drying Time:	Approx. 10 Minutes depending on temperature, humidity & subfloor
Storage & Shelf Life:	12 months in original, unopened container stored between +5°C and +25°C.
Container Size:	500 ml Can

F595 Vinyl Spray Adhesive

Safety Guidance:

Danger	F.595 Vinyl Spray Adhesive	UN1950
 	<p>DANGER Extremely flammable aerosol. Causes serious eye irritation. May cause drowsiness or dizziness. Pressurised container may burst if heated. Harmful to aquatic life with long lasting effects. Repeated exposure may cause skin dryness or cracking.</p> <p>Precautionary Statements Keep away from heat/sparks/open flames/hot surfaces. No Smoking Do not spray on an open flame or other ignition source. Pressurised container: Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing vapour/spray. Get medical advice/attention if you feel unwell. IF IN EYES: rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.</p>	
500ml	<p>CAUTION: Pressurised container. Protect from sunlight. Do not expose to temperatures exceeding 50°C. Do not pierce or burn even after use. Do not spray onto naked flame or any incandescent material.</p>	



A full materials safety data sheet relating to this product is available at www.floorwise.co.uk

This product data sheet is provided for guidance only. For further information and advice on application, or if in any doubt as to the suitability of the product for the installation, please contact our Technical Department for advice.