



## SAFETY DATA SHEET

### Floorwise F598

According to Regulation (EC) No 1907/2006, Annex II, as amended. Commission Regulation (EU) No 2015/830 of 28 May 2015.

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

Product name	Floorwise F598
Container size	500ml
REACH registration notes	All chemicals used in this product have been registered under REACH where required.

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Adhesive.
Uses advised against	Flexible PVC due to the risk of plasticiser migration.

##### 1.3. Details of the supplier of the safety data sheet

Supplier	Floorwise Group Ltd Floorwise House 22 High Street Kegworth Derby DE74 2DA Tel: 01509 673 974 Fax: 01509 674 841
----------	---

##### 1.4. Emergency telephone number

Emergency telephone	Floorwise: +44 (0) 1509 673 974 (Mon-Fri 09:00-17:00)
---------------------	---

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification (EC 1272/2008)

Physical hazards	Aerosol 1 - H222, H229
Health hazards	Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Carc. 2 - H351 STOT SE 3 - H336
Environmental hazards	Aquatic Chronic 3 - H412

##### 2.2. Label elements

###### Hazard pictograms



Signal word

Danger

## Floorwise F598

<b>Hazard statements</b>	H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated. H315 Causes skin irritation. H319 Causes serious eye irritation. H351 Suspected of causing cancer. H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting effects.
<b>Precautionary statements</b>	P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P261 Avoid breathing spray. P271 Use only outdoors or in a well-ventilated area. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P501 Dispose of contents/ container in accordance with national regulations.
<b>Contains</b>	DICHLOROMETHANE, Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane
<b>Supplementary precautionary statements</b>	P202 Do not handle until all safety precautions have been read and understood. P264 Wash contaminated skin thoroughly after handling. P273 Avoid release to the environment. P302+P352 IF ON SKIN: Wash with plenty of water. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308+P313 IF exposed or concerned: Get medical advice/ attention. P312 Call a POISON CENTRE/doctor if you feel unwell. P332+P313 If skin irritation occurs: Get medical advice/ attention. P337+P313 If eye irritation persists: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse. P403+P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up.

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB. In use may form flammable/explosive vapour-air mixture. Dichloromethane is converted to carbon monoxide in the body, which reduces the oxygen carrying capacity of the blood.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

<b>DICHLOROMETHANE</b>		<b>30-60%</b>
CAS number: 75-09-2	EC number: 200-838-9	REACH registration number: 01-2119480404-41
<b>Classification</b>		
Skin Irrit. 2 - H315		
Eye Irrit. 2 - H319		
Carc. 2 - H351		
STOT SE 3 - H336		

## Floorwise F598

<b>PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS</b> <b>&lt;0.1% 1,3 BUTADIENE</b> CAS number: 68476-85-7                      EC number: 270-704-2	<b>30-60%</b>
<b>Classification</b> Flam. Gas 1 - H220 Press. Gas (Liq.) - H280	
<b>Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, &lt;5% n-hexane</b> CAS number: —                                      EC number: 921-024-6                                      REACH registration number: 01-2119475514-35-XXXX	<b>1-5%</b>
<b>Classification</b> Flam. Liq. 2 - H225 Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	

The full text for all hazard statements is displayed in Section 16.

**Composition comments**                      CAS 68476-85-7 - Petroleum Gas, The substance contains less than 0.1% w/w 1,3-butadiene, meaning that the full harmonised classification regarding Muta. 1B H340 and Carc. 1A H350 does not apply.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>General information</b>	Move affected person to fresh air at once.
<b>Inhalation</b>	Move affected person to fresh air at once. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately.
<b>Ingestion</b>	Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention immediately.
<b>Skin contact</b>	Remove contaminated clothing immediately and wash skin with soap and water. Use hand wash which is specific to the removal of adhesive. Do not use solvents to clean skin.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention. If adhesive bonding occurs, do not force eyelids apart.
<b>Protection of first aiders</b>	No specific requirements are anticipated under normal conditions of use.

#### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.
<b>Inhalation</b>	Overexposure to organic solvents may depress the central nervous system, causing dizziness and intoxication and, at very high concentrations, unconsciousness and death.
<b>Ingestion</b>	Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract.
<b>Skin contact</b>	Prolonged contact may cause redness, irritation and dry skin. Contains components which may penetrate the skin. Product has a defatting effect on skin.

## Floorwise F598

**Eye contact** Irritation of eyes and mucous membranes.

### 4.3. Indication of any immediate medical attention and special treatment needed

**Specific treatments** If adhesive bonding occurs, do not force eyelids apart.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

**Suitable extinguishing media** Extinguish with alcohol-resistant foam, carbon dioxide or dry powder.

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Containers can burst violently or explode when heated, due to excessive pressure build-up. Forms explosive mixtures with air. May explode when heated or when exposed to flames or sparks. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.

**Hazardous combustion products** Thermal decomposition or combustion products may include the following substances: Toxic gases or vapours. Oxides of carbon. Phosgene (COCl<sub>2</sub>). Hydrogen chloride (HCl).

### 5.3. Advice for firefighters

**Protective actions during firefighting** Use water to keep fire exposed containers cool and disperse vapours. If a leak or spill has not ignited, use water spray to disperse vapours and protect men stopping the leak.

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Wear protective clothing as described in Section 8 of this safety data sheet. No smoking, sparks, flames or other sources of ignition near spillage. Avoid inhalation of vapours and contact with skin and eyes. If ventilation is inadequate, suitable respiratory protection must be worn.

**For non-emergency personnel** For the greatest protection, clothing should include anti-static overalls, boots and gloves.

**For emergency responders** For the greatest protection, clothing should include anti-static overalls, boots and gloves.

### 6.2. Environmental precautions

**Environmental precautions** Contain spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Contain spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses. Collect spillage for reclamation or disposal in sealed containers via a licensed waste contractor. Avoid water contacting spilled material or leaking containers. Approach the spillage from upwind. Take precautionary measures against static discharge. Use only non-sparking tools.

### 6.4. Reference to other sections

**Reference to other sections** Wear protective clothing as described in Section 8 of this safety data sheet. For waste disposal, see Section 13.

## Floorwise F598

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

<b>Usage precautions</b>	Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations. Do not use in confined spaces without adequate ventilation and/or respirator. Do not eat, drink or smoke when using this product.
<b>Advice on general occupational hygiene</b>	Do not eat, drink or smoke when using this product. Remove contaminated clothing and protective equipment before entering eating areas. Wash after use and before eating, smoking and using the toilet. Do not smoke in work area. Clean equipment and the work area every day.

#### 7.2. Conditions for safe storage, including any incompatibilities

<b>Storage precautions</b>	Under normal conditions of handling and storage, spillages from aerosol containers are unlikely. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Do not use containers made of the following materials: Aluminium. Pressurised container: may burst if heated Do not expose to temperatures exceeding 50°C/122°F. Protect from sunlight. Do not pierce or burn, even after use.
<b>Storage class</b>	Extremely Flammable Aerosol

#### 7.3. Specific end use(s)

<b>Specific end use(s)</b>	The identified uses for this product are detailed in Section 1.2.
----------------------------	---

### SECTION 8: Exposure controls/Personal protection

#### 8.1. Control parameters

##### Occupational exposure limits

##### DICHLOROMETHANE

Long-term exposure limit (8-hour TWA): WEL 100 ppm(Sk) 353 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 200 ppm(Sk) 706 mg/m<sup>3</sup>

##### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m<sup>3</sup>

WEL = Workplace Exposure Limit.

##### DICHLOROMETHANE (CAS: 75-09-2)

<b>DNEL</b>	Industry - Inhalation; Long term : 353 mg/m <sup>3</sup> Industry - Dermal; Long term : 4750 mg/kg/day Industry - Inhalation; Short term : 706 mg/m <sup>3</sup> Consumer - Inhalation; Long term : 88.3 mg/m <sup>3</sup> Consumer - Oral; Short term : 0.06 mg/kg/day Consumer - Inhalation; Short term : 353 mg/m <sup>3</sup> Consumer - Dermal; Short term : 2395 mg/kg/day
<b>PNEC</b>	- Fresh water; 0.54 mg/l - marine water; 0.194 mg/l - Sediment (Freshwater); 1.61 mg/kg - STP; 26 mg/l - Soil; 0.583 mg/kg - Intermittent release; 0.27 mg/l

##### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

## Floorwise F598

### DNEL

Consumer - Oral; Long term systemic effects: 699 mg/kg/day  
 Workers - Oral; Long term systemic effects: 2035 mg/kg/day  
 Consumer - Dermal; Long term systemic effects: 699 mg/kg/day  
 Workers - Dermal; Long term systemic effects: 773 mg/kg/day  
 Consumer - Inhalation; Long term systemic effects: 608 mg/m<sup>3</sup>

### 8.2. Exposure controls

#### Protective equipment



#### Appropriate engineering controls

Provide adequate ventilation. Ensure that the direction of airflow is clearly away from the worker. Use approved respirator if air contamination is above an acceptable level. Observe any occupational exposure limits for the product or ingredients. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof electrical, ventilating and lighting equipment. Ensure operatives are trained to minimise exposure.

#### Personal protection

Wear protective clothing.

#### Eye/face protection

Wear chemical splash goggles. Personal protective equipment for eye and face protection should comply with European Standard EN166.

#### Hand protection

Viton rubber (fluoro rubber). The selected gloves should have a breakthrough time of at least 2 hours. Minimum thickness: 0.7mm. To protect hands from chemicals, gloves should comply with European Standard EN374. The breakthrough time for any glove material may be different for different glove manufacturers. When used with mixtures, the protection time of gloves cannot be accurately estimated. Considering the data specified by the glove manufacturer, check during use that the gloves are retaining their protective properties and change them as soon as any deterioration is detected.

#### Other skin and body protection

Provide eyewash station. Avoid contact with skin. Wear suitable coveralls to prevent exposure to the skin.

#### Hygiene measures

Promptly remove any clothing that becomes contaminated. Wash promptly if skin becomes contaminated. Use appropriate hand lotion to prevent defatting and cracking of skin. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke.

#### Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. In confined or poorly-ventilated spaces, a supplied-air respirator must be worn. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible.

Gas filter, type AX. Short term

#### Thermal hazards

Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin.

#### Environmental exposure controls

Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

##### Appearance

Aerosol.

##### Colour

Amber.

## Floorwise F598

<b>Odour</b>	Chlorinated hydrocarbons.
<b>Odour threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point</b>	Not applicable.
<b>Initial boiling point and range</b>	Dichloromethane: 40°C @ 760 mm Hg
<b>Flash point</b>	A flash point method is not available but the major hazardous component, the Propellant has a flash point of <-60°C with flammability limits of 10.9% vol. upper and 1.4% vol. lower.
<b>Evaporation rate</b>	Dichloromethane: 27.5 (butyl acetate = 1)
<b>Evaporation factor</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	Not available.
<b>Other flammability</b>	Not available.
<b>Vapour pressure</b>	4-6 bar @ 20°C
<b>Vapour density</b>	Not available.
<b>Relative density</b>	Liquid base: ~1.18 @ 20°C
<b>Bulk density</b>	Not applicable.
<b>Solubility(ies)</b>	Insoluble in water.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition Temperature</b>	Data lacking.
<b>Viscosity</b>	Liquid base: 50-150 mPa s @ 20°C
<b>Explosive properties</b>	In use may form flammable/explosive vapour-air mixture.
<b>Explosive under the influence of a flame</b>	Yes
<b>Oxidising properties</b>	Does not meet the criteria for classification as oxidising.

### 9.2. Other information

**Volatile organic compound** This product contains a maximum VOC content of 612 g/l.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

**Reactivity** Vapours may form explosive mixtures with air.

### 10.2. Chemical stability

**Stability** Highly volatile.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** Will not polymerise. In use may form flammable/explosive vapour-air mixture.

### 10.4. Conditions to avoid

## Floorwise F598

**Conditions to avoid** Avoid heat, flames and other sources of ignition. Containers can burst violently or explode when heated, due to excessive pressure build-up. Avoid the accumulation of vapours in low or confined areas.

### 10.5. Incompatible materials

**Materials to avoid** Aluminium.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Toxic gases or vapours. Hydrogen chloride (HCl). Phosgene (COCl<sub>2</sub>). Carbon monoxide (CO).

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Skin corrosion/irritation

**Skin corrosion/irritation** Irritating to skin.

#### Serious eye damage/irritation

**Serious eye damage/irritation** Causes eye irritation.

#### Respiratory sensitisation

**Respiratory sensitisation** Based on available data the classification criteria are not met.

#### Skin sensitisation

**Skin sensitisation** Based on available data the classification criteria are not met.

#### Germ cell mutagenicity

**Genotoxicity - in vitro** Based on available data the classification criteria are not met.

**Genotoxicity - in vivo** Based on available data the classification criteria are not met.

#### Carcinogenicity

**Carcinogenicity** Suspected of causing cancer.

#### **IARC carcinogenicity**

IARC Group 2A Probably carcinogenic to humans.

#### Reproductive toxicity

**Reproductive toxicity - fertility** Based on available data the classification criteria are not met.

#### Specific target organ toxicity - single exposure

**STOT - single exposure** May cause drowsiness or dizziness.

#### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Based on available data the classification criteria are not met.

#### **General information**

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

#### **Inhalation**

High concentrations may be fatal. Prolonged inhalation of high concentrations may damage respiratory system. Vapours in high concentrations are narcotic. Vapours in high concentrations are anaesthetic.

#### **Ingestion**

Ingestion may cause severe irritation of the mouth, the oesophagus and the gastrointestinal tract. May cause nausea, headache, dizziness and intoxication.

#### **Skin contact**

Irritating to skin.

#### **Eye contact**

Irritating to eyes.



## Floorwise F598

**Acute and chronic health hazards** Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

**Route of exposure** Inhalation Skin absorption Ingestion

**Target organs** Central nervous system Respiratory system, lungs Liver

### Toxicological information on ingredients.

#### DICHLOROMETHANE

##### Acute toxicity - oral

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 2,000.1

**Species** Rat

**ATE oral (mg/kg)** 2,000.1

##### Acute toxicity - dermal

**Acute toxicity dermal (LD<sub>50</sub> mg/kg)** 2,000.1

**Species** Rat

**ATE dermal (mg/kg)** 2,000.1

##### Acute toxicity - inhalation

**Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l)** 86.0

**Species** Rat

**ATE inhalation (vapours mg/l)** 86.0

##### Skin corrosion/irritation

**Skin corrosion/irritation** Irritating to skin.

##### Serious eye damage/irritation

**Serious eye damage/irritation** Slightly irritating.

##### Respiratory sensitisation

**Respiratory sensitisation** There is evidence that the product can cause respiratory hypersensitivity.

##### Skin sensitisation

**Skin sensitisation** Not sensitising.

##### Germ cell mutagenicity

**Genotoxicity - in vitro** Genome mutation: Positive.

**Genotoxicity - in vivo** Chromosome aberration: Negative.

**General information** Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. Known or suspected carcinogen for humans.

## Floorwise F598

<b>Inhalation</b>	Harmful by inhalation. Vapours have a narcotic effect. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Nausea, vomiting. Irritating to respiratory system. Unconsciousness. High concentrations may be fatal. Vapours in high concentrations are anaesthetic.
<b>Ingestion</b>	May cause nausea, headache, dizziness and intoxication.
<b>Skin contact</b>	Prolonged contact may cause redness, irritation and dry skin. Product has a defatting effect on skin. May cause skin irritation/eczema.
<b>Eye contact</b>	Irritating to eyes.
<b>Acute and chronic health hazards</b>	Contains a substance which may be potentially carcinogenic.
<b>Route of exposure</b>	Inhalation Skin absorption Ingestion Skin and/or eye contact
<b>Target organs</b>	Central nervous system Liver Kidneys Skin Respiratory system, lungs Heart and cardiovascular system Eyes
<b>Medical symptoms</b>	Dilated pupils. Severe skin irritation. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Hypotension (low blood pressure). Unconsciousness, possibly death.
<b>Medical considerations</b>	Skin disorders and allergies. Liver and/or kidney damage. History of smoking. Convulsions. Central nervous system depression.

### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

<b>Toxicological effects</b>	Information given is based on data of the components and of similar products.
<b><u>Acute toxicity - oral</u></b>	
<b>Notes (oral LD<sub>50</sub>)</b>	Not applicable.
<b><u>Acute toxicity - dermal</u></b>	
<b>Notes (dermal LD<sub>50</sub>)</b>	Not applicable.
<b><u>Acute toxicity - inhalation</u></b>	
<b>Notes (inhalation LC<sub>50</sub>)</b>	LC <sub>50</sub> >20 mg/l, Inhalation, Rat
<b><u>Skin corrosion/irritation</u></b>	
<b>Skin corrosion/irritation</b>	Not irritating.
<b><u>Serious eye damage/irritation</u></b>	
<b>Serious eye damage/irritation</b>	Not irritating.
<b><u>Respiratory sensitisation</u></b>	
<b>Respiratory sensitisation</b>	Not sensitising.
<b><u>Skin sensitisation</u></b>	
<b>Skin sensitisation</b>	Not sensitising.
<b><u>Germ cell mutagenicity</u></b>	
<b>Genotoxicity - in vitro</b>	This substance has no evidence of mutagenic properties.
<b><u>Carcinogenicity</u></b>	
<b>Carcinogenicity</b>	Carcinogenicity in humans is not expected.

## Floorwise F598

### Reproductive toxicity

**Reproductive toxicity - fertility** Based on available data the classification criteria are not met.

**Reproductive toxicity - development** Does not contain any substances known to be toxic to reproduction.

### Specific target organ toxicity - single exposure

**STOT - single exposure** A single exposure may cause the following adverse effects: Overexposure to organic solvents may depress the central nervous system, causing dizziness and intoxication and, at very high concentrations, unconsciousness and death.

### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Not classified as a specific target organ toxicant after repeated exposure.

### Aspiration hazard

**Aspiration hazard** Not anticipated to present an aspiration hazard, based on chemical structure.

**Inhalation** May cause respiratory system irritation.

**Skin contact** Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin.

**Route of exposure** Inhalation Skin and/or eye contact

### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

### Acute toxicity - oral

**Acute toxicity oral (LD<sub>50</sub> mg/kg)** 5,000.0

**Species** Rat

### Acute toxicity - dermal

**Acute toxicity dermal (LD<sub>50</sub> mg/kg)** 2,000.0

**Species** Rabbit

### Skin corrosion/irritation

**Skin corrosion/irritation** Skin irritation.

### Serious eye damage/irritation

**Serious eye damage/irritation** Based on available data the classification criteria are not met.

### Respiratory sensitisation

**Respiratory sensitisation** Based on available data the classification criteria are not met.

### Skin sensitisation

**Skin sensitisation** Based on available data the classification criteria are not met.

### Germ cell mutagenicity

**Genotoxicity - in vitro** Based on available data the classification criteria are not met.

**Genotoxicity - in vivo** Based on available data the classification criteria are not met.

## Floorwise F598

### Carcinogenicity

**Carcinogenicity** Based on available data the classification criteria are not met.

### Specific target organ toxicity - single exposure

**STOT - single exposure** May cause drowsiness or dizziness.

### Specific target organ toxicity - repeated exposure

**STOT - repeated exposure** Based on available data the classification criteria are not met.

### Aspiration hazard

**Aspiration hazard** May be fatal if swallowed and enters airways.

## SECTION 12: Ecological information

**Ecotoxicity** The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

### Ecological information on ingredients.

#### DICHLOROMETHANE

**Ecotoxicity** The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

#### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

**Ecotoxicity** Information given is based on data of the components and of similar products.

### 12.1. Toxicity

**Toxicity** Not considered toxic to fish. Not regarded as dangerous for the environment.

### Ecological information on ingredients.

#### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

**Toxicity** Not regarded as dangerous for the environment. The product is not believed to present a hazard due to its physical nature. Highly volatile.

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

### Acute aquatic toxicity

**Acute toxicity - fish** LC<sub>50</sub>, : 1-10 mg/l, Fish  
NOEC, : 1-10 mg/l, Fish

**Acute toxicity - aquatic plants** LC<sub>50</sub>, : 10-100 mg/l, Algae

**Acute toxicity - microorganisms** LC<sub>50</sub>, : 1-10 mg/l, Activated sludge  
NOEC, : 0.1-1 mg/l, Activated sludge

### 12.2. Persistence and degradability

**Persistence and degradability** There are no data on the degradability of this product.

### Ecological information on ingredients.

#### DICHLOROMETHANE

## Floorwise F598

**Persistence and degradability** The substance is readily biodegradable.

### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

**Persistence and degradability** The product is readily biodegradable.

### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

**Persistence and degradability** No data available.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential** Bioaccumulation is unlikely.

### Ecological information on ingredients.

#### DICHLOROMETHANE

**Bioaccumulative potential** The product contains potentially bioaccumulating substances.

**Partition coefficient** log Pow: 1.25

### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

**Bioaccumulative potential** Bioaccumulation is unlikely.

### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

**Bioaccumulative potential** Not available.

### 12.4. Mobility in soil

**Mobility** The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

### Ecological information on ingredients.

#### DICHLOROMETHANE

**Mobility** The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces. The product is insoluble in water.

### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

**Mobility** The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.

### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** Not determined.

### Ecological information on ingredients.

#### DICHLOROMETHANE

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

## Floorwise F598

### PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS <0.1% 1,3 BUTADIENE

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

#### 12.6. Other adverse effects

**Other adverse effects** None known.

#### Ecological information on ingredients.

### DICHLOROMETHANE

**Other adverse effects** None known.

### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

**Other adverse effects** The product contains a substance which is toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**Disposal methods** Do not puncture or incinerate, even when empty. Avoid the spillage or runoff entering drains, sewers or watercourses. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.

**Waste class** Full or Partially Empty Aerosol: 16 05 04, Empty Aerosol: 15 01 10 (Containing hazardous residues), Empty Aerosol: 15 01 04 (No hazardous residues).

## SECTION 14: Transport information

### 14.1. UN number

**UN No. (ADR/RID)** 1950

**UN No. (IMDG)** 1950

**UN No. (ICAO)** 1950

**UN No. (ADN)** 1950

### 14.2. UN proper shipping name

**Proper shipping name (ADR/RID)** AEROSOLS

**Proper shipping name (IMDG)** AEROSOLS

**Proper shipping name (ICAO)** AEROSOLS

**Proper shipping name (ADN)** AEROSOLS

### 14.3. Transport hazard class(es)

**ADR/RID class** 2.1

**ADR/RID classification code** 5F

**ADR/RID label** 2.1

**IMDG class** 2.1

**ICAO class/division** 2.1

## Floorwise F598

**ADN class** 2.1

### Transport labels



### 14.4. Packing group

Not applicable.

### 14.5. Environmental hazards

#### Environmentally hazardous substance/marine pollutant

No.

### 14.6. Special precautions for user

**IMDG Code segregation group** SG69

**EmS** F-D, S-U

**ADR transport category** 2

**Tunnel restriction code** (D)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not relevant.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**National regulations** Health and Safety at Work etc. Act 1974 (as amended).  
The Control of Substances Hazardous to Health Regulations 2002 (SI 2002 No. 2677) (as amended).  
The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).

**EU legislation** Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).  
Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

**Guidance** Workplace Exposure Limits EH40.

**Authorisations (Annex XIV Regulation 1907/2006)** No specific authorisations are known for this product.

**Restrictions (Annex XVII Regulation 1907/2006)** No specific restrictions on use are known for this product.

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### Inventories

## Floorwise F598

### EU - EINECS/ELINCS

All the ingredients are listed or exempt.

### Canada - DSL/NDSL

Some of the ingredients are listed or exempt.

### US - TSCA

Some of the ingredients are listed or exempt.

### US - TSCA 12(b) Export Notification

None of the ingredients are listed or exempt.

### Australia - AICS

Some of the ingredients are listed or exempt.

### Japan - ENCS

Some of the ingredients are listed or exempt.

### Korea - KECI

Some of the ingredients are listed or exempt.

### China - IECSC

Some of the ingredients are listed or exempt.

### Philippines – PICCS

Some of the ingredients are listed or exempt.

### New Zealand - NZIOC

Some of the ingredients are listed or exempt.

### Taiwan - TCSI

Some of the ingredients are listed or exempt.

## SECTION 16: Other information

<b>Classification procedures according to Regulation (EC) 1272/2008</b>	Aerosol 1 - H222, H229: Weight of evidence. Carc. 2 - H351: Calculation method. Skin Irrit. 2 - H315: Calculation method. STOT SE 3 - H336: Calculation method. Aquatic Chronic 3 - H412: Calculation method.
<b>Issued by</b>	Technical Department
<b>Revision date</b>	20/04/2020
<b>Revision</b>	10
<b>Supersedes date</b>	28/02/2017
<b>SDS number</b>	11733



## Floorwise F598

### Hazard statements in full

H220 Extremely flammable gas.  
H222 Extremely flammable aerosol.  
H225 Highly flammable liquid and vapour.  
H229 Pressurised container: may burst if heated.  
H280 Contains gas under pressure; may explode if heated.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H351 Suspected of causing cancer.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.