

FloorPly

Floorwise FloorPly has been specifically developed to provide installers with a premium quality flooring grade plywood that fully complies with the requirements of BS 8203.

- TFT WOODEXPERTS Diamond Mark Certified
- Compliant with CFA Guidance
- Available in 3.6mm, 5.5mm and 9.0mm
- Made from responsibly sourced timber
- BS EN 314-2 Class 3 exterior glue
- Excellent dimensional accuracy
- 0.80mm thick veneers after sanding
- Two sheet sizes available



Description:

FloorPly is a premium BS8203 compliant Flooring Grade plywood with both outer veneers and core manufactured from tropical Okoume hardwood to give a stable, durable substrate suitable for use with most interior flooring applications.

Product Specification:

TFT Diamond Mark	Certified
Average Density	500kg/m ³
Wood Species	Tropical Okoume timber throughout
Appearance	Free from knots and core gaps
Durability Classification	EN 636-2
Glue Bond	EN 314-2 Class 3 Exterior
Formaldehyde Emission Class	EN 636-2 – E1
Board Sizes (mm)	2440 x 1220 / 1220 x 610
Dimensional Accuracy	Compliant with EN 315
Thicknesses Available (mm)	3.6 / 5.5 / 9.0
External Veneer Thickness (mm)	0.80 ±0.02
Moisture Content (After Production)	8% to 10%
Responsibly Sourced Timber	Yes
UKCA Marked	BS EN 13986